














	PE50-PRO	VI100-PRO	POX150-PRO	CAPSULE
				
Tipuri de amestec	POLY ESTER	VINYL ESTER	100% PURE EPOXY	VINYL ESTER
Pagina	137	138	139	140
Dozare	165, 300 si 400 ml	165, 300 si 400 ml	265 si 470 ml	M8 - M24
INCARCARE				
Sarcini mari		✓	✓	✓
Sarcini medii-mari	✓	✓		✓
Sarcini medii	✓			
CERTIFICARE				
ETA zidarie	✓			
ETA optiunea 7			✓	
ETA optiunea 8				✓
ETA optiunea 1		✓	✓	
ETA fier-beton		✓	✓	
SPECIFICATII				
Validat pentru fixare tija filetata	M8-M12	M8-M24	M8-M30	M8-M24
Validat pentru fixare fier-beton		Ø8 - Ø32	Ø8 - Ø32	
Validat pentru fixare in profunzime		✓	✓	4xØ - 20xØ
Validat pentru fixare in mediu umed		✓	✓	M8-M30, Ø8 - Ø30
Uscare rapide	✓	✓		
APLICATII SPECIFICE				
Temperatura de utilizare	0 la +30°C	-10 la +40°C	0 la +30°C	-5°C la +35°C
Zone umede		✓	✓	✓
Gauri inundate		✓	✓	
Actiuni seismice		In curs	In curs	
PISTOL ALSAFIX/PANASONIC				
Pistol 300 ml	✓	✓	✓	
Pistol 400 ml	✓	✓		
Pistol 470 ml			✓	
EY3610LA	✓	✓	✓	
EY3640LS	✓	✓	✓	
PISTOL COMPATIBIL				
Hilti			✓	
Fischer/Upat	✓	✓	✓	
Spit/Mungo/MEA	✓	✓	✓	
MATERIALE SUPORT				
Beton nefisurat 	✓	✓	✓	✓
Beton fisurat 		✓	✓	✓
Piatra naturala 		✓	✓	✓
Silico-calcar solid 	✓	✓		✓
Caramida plina 	✓	✓		✓
Caramida cu goluri 	✓	✓		
Lemn 		✓	✓	
ALTE SPECIFICATII				
Fara miros	✓	✓		✓
Retragerea neglijabila			✓	✓
Fara stiren	✓	✓	✓	✓
Termen de valabilitate	12 luni	12 luni	24 luni	24 luni